



REL ALT 3 5 10 20 ABOVE BRT

FL RANGE NORM BELOW OFF MAX

Arrows indicate that the target is climbing ↑ or descending ↓ at a rate of at least 500 fpm.	
Relative altitude is displayed in the proximity of the aircraft symbol in hundreds of feet. A "+" preceding the relative altitude indicates the target is above you, and a "-" indicates it is below you.	
Displayed Aircraft Symbols (Examples)	
	<i>Unfilled white diamond.</i> Non-threatening traffic without altitude reporting. If altitude reporting, the altitude data will be displayed.
	<i>Solid white diamond.</i> Proximity traffic 700 feet above. Non-threatening, altitude reporting traffic within 1200 feet vertically and 6nm horizontally. Aircraft without altitude reporting will be assumed to be co-altitude and will be displayed as a solid diamond when within 6nm even though they may not be within 1200 feet vertically.
	<i>Solid yellow circle.</i> "TA", 300 feet below, descending. At least 500 FPM.
	<i>Solid red square.</i> "RA", level at your altitude.
	<i>Ownship.</i> Airplane symbol in white just below the center of CRT. On a dedicated display or when in the TFC Mode on a combination TCAS/RADAR Display.
(Compass Arc)	This arc is a repeater of the Captains compass. (Not required for a TCAS II Display).
(Range Rings)	3nm - Small ring with ticks at clock positions 5 NM - Large ring made of dots.